



GT Series Specs

Last Updated 2/23/06

Tractor Model	GT45A	GT55A	GT65A	GT75A
CONFIGURATION				
Drive System	2WD or 4WD	2WD or 4WD	2WD or 4WD	2WD or 4WD
Operator Area	Platform or Cab	Platform or Cab	Platform or Cab	Platform or Cab
PERFORMANCE				
*Engine HP (kW) @ Rated Engine RPM	52.0 (38.5) @ 2200	66.0 (49.2) @ 2200	71.0 (52.9) @ 2200	83.0 (61.0) @ 2200
*PTO HP (kW) @ Rated Engine RPM	44.0 (32.8) @ 2200	56.0 (41.8) @ 2200	62.0 (46.2) @ 2200	74.0 (54.0) @ 2200
Fuel Tank Capacity Gallons (L)	23.7 (89.7)	23.7 (89.7)	23.7 (89.7)	23.7 (89.7)
ENGINE				
Number of Cylinders / Aspiration	3-Cylinder / Natural	3-Cylinder / Turbo	4-Cylinder / Natural	4-Cylinder / Turbo
Type of Cooling / Fuel	Water / Diesel	Water / Diesel	Water / Diesel	Water / Diesel
Total Displacement Liters (in3)	3.0 (183)	3.0 (183)	4.0 (244)	4.0 (244)
Starting Aid	Thermostart	Thermostart	Thermostart	Thermostart
STANDARD TRANSMISSION				
Type	Synchro-Shuttle	Synchro-Shuttle	Synchro-Shuttle	Synchro-Shuttle
Speeds Forward/Reverse	20F / 10R	20F / 10R	20F / 10R	20F / 10R
Clutch	Dry Single Disc	Dry Single Disc	Dry Single Disc	Dry Single Disc
BRAKES & FINAL DRIVES				
Type of Final Drives	Internal Planetary	Internal Planetary	Internal Planetary	Internal Planetary
Type of Brakes	Wet Disc	Wet Disc	Wet Disc	Wet Disc
Type of Differential Lock	Sliding Pin	Sliding Pin	Sliding Pin	Sliding Pin
PTO				
Type	Independent	Independent	Independent	Independent
Speeds (rpm)	540/1000	540/1000	540/1000	540/1000
Engagement	Electro-Hydraulic	Electro-Hydraulic	Electro-Hydraulic	Electro-Hydraulic
2WD FRONT AXLE				
Axle Type	Telescopic	Telescopic	Telescopic	Telescopic
4WD FRONT AXLE				
4WD Engagement	Electro-Hydraulic	Electro-Hydraulic	Electro-Hydraulic	Electro-Hydraulic
Type of Differential Lock	Sliding Pin	Sliding Pin	Sliding Pin	Sliding Pin
Max. Steering Angle	55 deg.	55 deg.	55 deg.	55 deg.
HYDRAULICS				
System Type	Open Center	Open Center	Open Center	Open Center
Total Flow gpm (Lpm)	22.7 (86.0)	22.7 (86.0)	22.7 (86.0)	22.7 (86.0)
Flow @ Remotes gpm (Lpm)	14.0 (53.0)	14.0 (53.0)	14.0 (53.0)	14.0 (53.0)
Remotes (Std/Opt)	2/3	2/3	2/3	2/3



GT Series Specs

Last Updated 2/23/06

THREE-POINT HITCH

ASAE Category	Cat II	Cat II	Cat II	Cat II
Stabilizers	Telescopic	Telescopic	Telescopic	Telescopic
Lower Draft Arm Link Ends Std (Opt)	Fixed (Extendable)	Fixed (Extendable)	Fixed (Extendable)	Fixed (Extendable)
Lift Capacity @ 24" lbs (kg)	3520 (1597)	3520 (1597)	3520 (1597)	3520 (1597)

OPERATOR AREA

Cab Glass Area ft2 (m2)	44 (4.18)	44 (4.18)	44 (4.18)	44 (4.18)
Cab Doors	2 Standard	2 Standard	2 Standard	2 Standard
Steering Wheel - Platform / Cab	Tilt / Tilt & Telescopic	Tilt / Tilt & Telescopic	Tilt / Tilt & Telescopic	Tilt / Tilt & Telescopic
Transmission Control	Right Side	Right Side	Right Side	Right Side
Seat Suspension	Mechanical Adjustable	Mechanical Adjustable	Mechanical Adjustable	Mechanical Adjustable

DIMENSIONS & WEIGHT

Wheelbase 2WD / 4WD in (mm)	82.9 / 80.9 (2105 / 2055)	82.9 / 80.9 (2105 / 2055)	88 / 86 (2235 / 2184)	88 / 86 (2235 / 2184)
Overall Length in (mm)	145.7 (3700)	145.7 (3700)	151.6 (3850)	151.6 (3850)
Min Overall Width in (mm)	70.4 (1788)	70.4 (1788)	76.7 (1948)	78 (1981)
Height Over ROPS/Cab in (mm)	97.2 / 103.6 (2469 / 2631)	98.2 / 104.6 (2469 / 2631)	99.6 / 106 (2530 / 2692)	99.6 / 106 (2530 / 2692)
Treadwidth - Front 2WD in (mm)	54.6 - 66.4 (1387 - 1687)	54.6 - 66.4 (1387 - 1687)	54.6 - 66.4 (1387 - 1687)	54.6 - 66.4 (1387 - 1687)
Treadwidth - Front 4WD in (mm)	57.5 - 69.1 (1460 - 1755)	57.5 - 69.1 (1460 - 1755)	57.3 - 73 (1455 - 1855)	57.3 - 73 (1455 - 1855)
Treadwidth - Rear in (mm)	55.1 - 74.8 (1400 - 1900)	55.1 - 74.8 (1400 - 1900)	59 - 74.8 (1500 - 1900)	59 - 74.8 (1500 - 1900)
Turn Radius ft (m)	10 / 12 (3.0 / 3.7)	10 / 12 (3.0 / 3.7)	10.8 / 12.5 (3.3 / 3.8)	10.8 / 12.5 (3.3 / 3.8)
Approx. Weight 2wd Plat. lbs (kg)	4806 (2180)	4982 (2260)	5335 (2420)	5511 (2500)
Approx. Weight 4wd Plat. lbs (kg)	5291 (2400)	5467 (2480)	5820 (2640)	5996 (2720)
Approx. Weight 2wd Cab lbs (kg)	5335 (2420)	5511 (2500)	5864 (2660)	6040 (2740)
Approx. Weight 4wd Cab lbs (kg)	5820 (2640)	5996 (2720)	6350 (2880)	6525 (2960)

*Manufacturer's Estimates