

MODELS	5134	5145	5146	5156	5545	5546	5556	5546A AUTO-CYCLE	5556A AUTO-CYCLE
<b>Bale Size</b>									
Diameter - min. in (mm)	30 (762)	30 (762)	30 (762)	30 (762)	30 (762)	30 (813)	30 (762)	30 (813)	32 (813)
Diameter - max. in (mm)	52 (1,321)	62 (1,575)	72 (1,829)	72 (1,829)	60 (1,524)	72 (1,829)	72 (1,829)	72 (1,829)	72 (1,829)
Width in (mm)	39 (991)	46.5 (1,182)	46.5 (1,182)	61.5 (1,562)	46.5 (1,182)	46.5 (1,182)	61.5 (1,562)	46.5 (1,182)	61.5 (1,562)
Weight - Dry - lb (kg)	550 (249)	1,250 (567)	1,500 (680)	2,100 (953)	1,140 (518)	1,644 (746)	2,200 (998)	1,644 (746)	2,200 (998)
Weight - Max. Silage - lb (kg)	N.A.	N.A.	N.A.	N.A.	2,000 (907)	2,200 (998)	2,400 (1,089)	2,200 (998)	2,400 (1,089)
<b>Dimensions &amp; Weights</b>									
Overall Width in (mm)	74.5 (1,892)	92.5 (2,350)	100 (2,550)	112 (2,845)	102.5 (2,604)	102.5 (2,604)	117.5 (2,985)	102.5 (2,604)	117.5 (2,985)
Overall Length in (mm)	132 (3,353)	147 (3,734)	162 (4,115)	162 (4,115)	149 (3,768)	149 (3,768)	155 (3,937)	149 (3,768)	155 (3,937)
Overall Height in (mm)	84 (2,134)	101 (2,565)	118 (3,000)	118 (3,000)	103 (2,616)	115 (2,921)	115 (2,921)	115 (2,921)	115 (2,921)
Weight lb (kg)	2,780 (1,261)	3,720 (1,687)	5,100 (2,313)	5,380 (2,440)	5,720 (2,595)	6,120 (2,776)	6,750 (3,057)	6,120 (2,776)	6,800 (3,085)
Tongue Weight lb (kg)	500 (227)	440 (200)	1,120 (508)	1,250 (569)	1,100 (580)	1,150 (571)	1,340 (617)	1,150 (571)	1,560 (708)
Tire Size	7.60 x 15	11L x 15	31 x 13.5 - 15	31 x 13.5 - 15	31 x 13.5-15	14L x 16.1	14L x 16.1	14L x 16.1	14L x 16.1
Optional Tires	N.A.	N.A.	14L - 16.1	14L - 16.1	N.A.	N.A.	N.A.	N.A.	N.A.
<b>Bale Chamber</b>									
Number of Belts	5 Laced, MiniGrip Pattern	6 Laced, WedgeGrip Pattern	6 Laced, WedgeGrip Pattern	8 Laced, WedgeGrip Pattern	6 Laced, WedgeGrip Pattern	6 Laced, WedgeGrip Pattern	8 Laced, WedgeGrip Pattern	6 Laced, WedgeGrip Pattern	8 Laced, WedgeGrip Pattern
Belt Width in (mm)	4.8 (122)	7.0 (178)	7.0 (178)	7.0 (178)	7.0 (177)	7.0 (177)	7.0 (177)	7.0 (177)	7.0 (177)
Bale Size Indicator	Visual Gauge	Visual Gauge	Visual Gauge	Visual Gauge	Monitor & Visual On-baler	Monitor & Visual On-baler	Monitor & Visual On-baler	Monitor & Visual On-baler	Monitor & Visual On-baler
Bale Shape Indicator	N.A.	N.A.	3 Driving Lights	3 Driving Lights	3 Colored Bars on Monitor	3 Colored Bars on Monitor	3 Colored Bars on Monitor	Arrows on Monitor	Arrows on Monitor
Oversize Bale Protection	Audible Warning	N.A.	Audible Warning	Audible Warning	Audible & Visible Indication	Audible & Visible Indication	Audible & Visible Indication	Declutches Baler	Declutches Baler
<b>Pickup</b>									
Width - Tine to Tine - in (mm)	33.8 (858)	44.17 (1,122)	44.17 (1,122)	59.8 (1,518)	60 (1,518)	60 (1,518)	75.3 (1,914)	60 (1,518)	75.3 (1,914)
Width - Inside, Panel to Panel - in (mm)	38.0 (965)	55.8 (1,417)	46.8 (1,188)	61.8 (1,568)	66 (1,680)	66 (1,680)	83.6 (2,123)	66 (1,680)	83.6 (2,123)
Width - Outside End to End - in (mm)	38.8 (986)	65 (1,651)	57 (1,448)	72 (1,830)	78 (1,981)	78 (1,972)	92 (2,337)	78 (1,972)	92 (2,337)
Tine Bars	3	4	4	4	4 (2 per Row)	4 (2 per Row)	4 (2 per Row)	4 (2 per Row)	4 (2 per Row)
Number of Tines	42	72	72	72	96	96	120	96	120
Windguard	Rod	Adjustable Rod	Adjustable Rod	Adjustable Rod	Adjustable Rod	Adjustable Rod	Adjustable Rod	Adjustable Rod	Adjustable Rod
<b>Bale Wrapping</b>									
Twine Wrapping	Manually - Rope Actuated Twine	Electric Actuated (Auto-Tie Opt)	Auto, Electric Actuated	Auto, Electric Actuated	Auto, Electric Actuated	Auto, Electric Actuated	Auto, Electric Actuated	Auto, Hydraulic Actuated	Auto, Hydraulic Actuated
Number of Twine Balls - Depending on Size	2	4	4	4	Up to 8	Up to 8	Up to 8	Up to 8	Up to 8
Mesh Wrap	N.A.	N.A.	Factory/Field Opt	Factory/Field Opt	Factory or Field Opt	Factory/Field Opt	Factory/Field Opt	Factory Opt	Factory Opt
<b>Tractor Requirements</b>									
Horsepower - Min - hp (kW)	30 (22)	40 (30)	55 (41)	70 (52.2)	55 (41)	65 (49)	70 (52)	65 (49)	70 (52)
Tractor Weight - Min - lbs (kgs)	3,000 (1,361)	4,000 (1,814)	6,000 (2,722)	7,000 (3,175)	6,000 (2,722)	6,500 (2,948)	7,000 (3,175)	6,500 (2,948)	7,000 (3,175)
PTO Speed (rpm)	540	540	540 (1000 w/ Conversion)	540 (1000 w/ Conversion)	540 (1000 w/ Conversion)	540 (1000 w/ Conversion)	540 or 1000	540 (1000 w/ Conversion)	540 or 1000
Hydraulic Remote Valves	One Double Acting	One Double Acting	One Double Acting	One Double Acting	One Double Acting	One Double Acting	One Double Acting	None Required	None Required
<b>Optional Kits</b>									
	Fire Extinguisher	Fire Extinguisher	Fire Extinguisher	Fire Extinguisher	Fire Extinguisher	Fire Extinguisher	Fire Extinguisher	Fire Extinguisher	Fire Extinguisher
	Gathering Wheels	Gathering Wheels	Gathering Wheels	Gathering Wheels	Short Crop Kit	Short Crop Kit	Short Crop Kit	Short Crop Kit	Short Crop Kit
	Bale Ramp	Bale Ramp	Bale Kicker	Bale Kicker	Hydraulic Bale Ejector	Hydraulic Bale Ejector	Hydraulic Bale Ejector	Silage Kit (Non-Silage Balers)	Silage Kit
	Electric Threader	Starting Roll Scraper	Bale Ramp	Bale Ramp	Hydraulic Pickup Lift	Hydraulic Pickup Lift	Hydraulic Pickup Lift		
		Remote Cycle Start (Auto-Tie)	Mesh Wrap	Mesh Wrap	Silage Kit (Non-Silage Balers)	Silage Kit (Non-Silage Balers)	Silage Kit		
		Bale Counter			Mesh Wrap	Mesh Wrap	Mesh Wrap		